




Geberit WC flush control with electronic flush actuation, mains operation, for Sigma concealed cistern 12 cm, dual flush, with Sigma80 actuator plate, square, touchless



APPLICATION PURPOSES

- For private and semipublic areas
- For releasing a dual flush
- For solid and drywall construction
- For touchless flush actuation of Sigma concealed cisterns 12 cm
- Not suitable for use with Geberit inserts for in-cistern block
- Suitable for barrier-free construction

CHARACTERISTICS

- Flush actuation possible via external push-button
- Actuator plate without mechanical buttons
- Actuator buttons identifiable by light bars
- Button illumination activated when approached
- Button illumination can be set in five colours
- Orientation light can be activated

- Power supply via external power supply unit
- Transformation of mains voltage to extra-low voltage, 12 V DC
- Operation with extra-low voltage, no mains voltage in cistern
- Adjustable interval flush
- Preflush can be set
- Minimum detection time can be set
- Device settings and operation with mobile device via integrated Bluetooth® interface
- Compatible with Geberit Control App
- Wired networkable with Geberit gateway via GEBUS converter
- Wirelessly connectable with Geberit Gateway via Bluetooth®
- Compatible with Geberit Connect
- Compatible with Geberit Service Handy
- Lockable

TECHNICAL DATA

Protection degree IP45

Nominal voltage	85–240 V AC
Operating voltage	12 V DC
Mains frequency	50–60 Hz
Power consumption standby	0.15 W
Interval flush time, factory setting	5 s
Detection time, factory setting	7 s

SCOPE OF DELIVERY

- Sigma80 actuator plate
- Mounting frame
- Support block with servomotor and lifting device, premounted

TO ORDER ADDITIONALLY

- Geberit power supply unit for Power & Connect box

<i>Art. no.</i>	<i>Colour / surface</i>	<i>Product material</i>	<i>B</i> cm	<i>H</i> cm	<i>T</i> cm	<i>Power consumption</i> W
116.090.SG.6	black / glass	Glass	24.7	16.4	1	≤ 4